



Hose Barb to SAE Flange Head




- Suction to 400 psi max
- Carbon steel natural finish
- Material certificates available upon request
- Flange head manufactured to SAE J518-1



90° HOSE BARB TO SAE FLANGE HEAD							
	HOSE SIZE	FLANGE SIZE	A	B	C	ID	SPLIT FLANGE
20HB-20SF90	1.25	1.25	4.64	3.13	2.00	1.03	20SFO
24HB-24SF90	1.50	1.50	5.00	3.50	2.38	1.28	24SFO
32HB-32SF90	2.00	2.00	6.19	4.25	2.81	1.75	32SFO
40HB-40SF90	2.50	2.50	7.50	5.50	3.31	2.17	40SFO
48HB-48SF90	3.00	3.00	8.75	6.38	4.00	2.72	48SFO
64HB-64SF90	4.00	4.00	10.75	7.75	5.00	3.69	64SFO



45° HOSE BARB TO SAE FLANGE HEAD							
	HOSE SIZE	FLANGE SIZE	A	B	C	ID	SPLIT FLANGE
20HB-20SF45	1.25	1.25	2.66	4.91	2.00	1.03	20SFO
24HB-24SF45	1.50	1.50	2.74	5.12	2.38	1.28	24SFO
32HB-32SF45	2.00	2.00	3.23	5.85	2.81	1.75	32SFO
40HB-40SF45	2.50	2.50	3.89	7.39	3.31	2.17	40SFO
48HB-48SF45	3.00	3.00	4.42	8.30	4.00	2.72	48SFO
64HB-64SF45	4.00	4.00	5.13	9.38	5.00	3.69	64SFO



STRAIGHT HOSE BARB TO SAE FLANGE HEAD						
	HOSE SIZE	FLANGE SIZE	A	B	ID	SPLIT FLANGE
20HB-20SF	1.25	1.25	3.39	2.00	1.03	20SFO
24HB-24SF	1.50	1.50	3.50	2.38	1.28	24SFO
32HB-32SF	2.00	2.00	3.93	2.81	1.75	32SFO
40HB-40SF	2.50	2.50	4.63	3.31	2.17	40SFO
48HB-48SF	3.00	3.00	5.19	4.00	2.72	48SFO
64HB-64SF	4.00	4.00	5.83	5.00	3.69	64SFO

† Optional Split Flange sold separately