



Hose Barb to SAE Thread


- Suction to 400 PSI max
- Buna seals standard / Viton optional
- Carbon steel natural finish
- 90° & 45° SAE thread with adjustable nut
- Material certificates available upon request
- SAE threads manufactured to J1926



90° HOSE BARB TO SAE THREAD							
	HOSE SIZE	THREAD SIZE	A	B (REF.)	C	ID	BALL VALVE
20HB-20SAE90	1.25	1.25	4.64	3.28	1 5/8-12	1.03	LV2BS#20-2T-MH
*24HB-24SAE90	1.50	1.50	5.00	3.65	1 7/8-12	1.28	LV2BS#24-2T-MH
*32HB-32SAE90	2.00	2.00	6.19	4.40	2 1/2-12	1.58	LV2BS#32-2T-MH
*40HB-40SAE90	2.50	2.50	7.50	5.23	3-12	2.09	LV2BS#40-2T-MH
*48HB-48SAE90	3.00	3.00	8.75	6.15	3 1/2-12	2.48	LV2BS#48-2T-MH
*64HB-64SAE90	4.00	4.00	10.75	7.65	4 1/2-12	3.69	LV2BS#64-2T-MH



45° HOSE BARB TO SAE THREAD							
	HOSE SIZE	THREAD SIZE	A	B (REF.)	C	ID	BALL VALVE
20HB-20SAE45	1.25	1.25	2.66	5.11	1 5/8-12	1.03	LV2BS#20-2T-MH
*24HB-24SAE45	1.50	1.50	2.74	5.31	1 7/8-12	1.28	LV2BS#24-2T-MH
*32HB-32SAE45	2.00	2.00	3.23	6.05	2 1/2-12	1.58	LV2BS#32-2T-MH
*40HB-40SAE45	2.50	2.50	3.89	7.18	3-12	2.09	LV2BS#40-2T-MH
*48HB-48SAE45	3.00	3.00	4.42	8.13	3 1/2-12	2.48	LV2BS#48-2T-MH
*64HB-64SAE45	4.00	4.00	5.13	9.34	4 1/2-12	3.69	LV2BS#64-2T-MH



STRAIGHT HOSE BARB TO SAE THREAD							
	HOSE SIZE	THREAD SIZE	A	B	C	ID	BALL VALVE
20HB-20SAE	1.25	1.25	2.00	3.01	1 5/8-12	1.03	LV2BS#20-2T-MH
24HB-24SAE	1.50	1.50	2.50	3.01	1 7/8-12	1.28	LV2BS#24-2T-MH
32HB-32SAE	2.00	2.00	3.25	3.45	2 1/2-12	1.58	LV2BS#32-2T-MH
40HB-40SAE	2.50	2.50	3.75	4.01	3-12	2.09	LV2BS#40-2T-MH
48HB-48SAE	3.00	3.00	4.50	4.63	3 1/2-12	2.48	LV2BS#48-2T-MH
64HB-64SAE	4.00	4.00	5.50	5.13	4 1/2-12	3.69	LV2BS#64-2T-MH

* Uses Adjustable Spanner
 † Optional Ball Valve sold separately

