

DESCRIPTION

Single Acting, Normally Closed (NC) - Inlet Under Seat

PRESENTATION

- Compact valve
- Water hammer effect prevention
- Protected visual position indicator
- PTFE sealing pack
- from 3/8" up to 3" (4" ND100mm on request)
- NPT thread on request
- Maintenance free sealing pack
- Normally open version available on request
- Double acting version available on request
- Pilot thread: 1/8" (1/4" for 125mm actuators) BSP or NPT
- Universal mounting position




USE: Packaging, Beverage equipment, Food processing, Textile printing & Dyeing, Gas industry, Pharmacy & Medical Equipment, Chemical industry, Disinfection, Foaming Equipment, Water/sewage Disposal

CONNECTION: Threaded (BSP or NPT)

5

VALVE FEATURES

Fluid Pressure	Up to max 232psi (16bar)
Control Pressure	50 - 87psi (3.5 - 6bar)(see table)
Control Fluid	Neutral gas, Air
Body material	Stainless steel AISI 316
Sealing	PTFE
Actuator Material	AISI 304 or Aluminium for 4.9inches actuator
Actuator Size	1.6 - 2 - 2.5 - 3.5 - 4.9 inches (40 - 50 - 63 - 90 - 125 mm)
Fluids	Water, Alcohol, Oils, Fuels, Steam, Natural gases or Liquids, Organic solvents, Acids and Lyes
Fluid viscosity	Max 600cSt (mm ² /s)
Fluid temperature	14°F +356°F (-10°C to +180°C)
Ambient temperature	14°F +176°F (-10°C to +80°C)
Control Type	Normally closed, (on request Normally open, Double acting)



For piloting please use the solenoid valve E311ANB15///U35D (3/2NC, Ø1.5, 120V AC UL approved)

OVERALL DIMENSIONS

CODE	G	Actuator		Nominal Diameter		Pilot Pressure		Max Pressure		Q	C	R	K	T	A	L	SW
		inches	mm	inches	mm	psi	bar	psi	bar								
PE140CGW10/V	3/8"	1.57	40	0.39	10	58	4	188	13	1/8"	1.99	1.06	4.41	0.47	4.88	2.68	1.06
PE150CGW10/V		1.97	50			65	4.5	203	14	1/8"	2.36	1.30	4.92		5.31		
PE140DGW15/V	1/2"	1.57	40	0.59	15	58	4	188	13	1/8"	1.99	1.06	4.41	0.47	4.88	2.68	1.06
PE150DGW15/V		1.97	50			65	4.5	203	14	1/8"	2.36	1.30	4.92		5.31		
PE150EGW20/V	3/4"	1.97	50	0.79	20	65	4.5	203	14	1/8"	2.36	1.30	5.20	0.63	5.51	2.95	1.26
PE150FGW25/V	1"	1.97	50	1	25	65	4.5	116	8	1/8"	2.36	1.30	5.35	0.67	5.91	3.54	1.57
PE163FGW25/V		2.48	63			72.5	5	188	13	1/8"	2.95	1.61	6.38		6.77		
PE190FGW25/V		3.54	90			50	3.5	203	14	1/8"	4.17	2.17	8.78		9.25		
PE163GGW32/V	1 1/4"	2.48	63	1.26	32	72.5	5	87	6	1/8"	2.95	1.61	6.85	0.83	7.48	4.57	1.97
PE190GGW32/V		3.54	90			87	6	232	16	1/8"	4.17	2.17	8.78		9.25		
PE163HGW40/V	1 1/2"	2.48	63	1.57	40	72.5	5	72.5	5	1/8"	2.95	1.61	6.89	0.83	7.48	4.57	2.20
PE190HGW40/V		3.54	90			87	6	232	16	1/8"	4.17	2.17	8.78		9.25		
PE163IGW50/V	2"	2.48	63	2	50	72.5	5	43.5	3	1/8"	2.95	1.61	7.20	0.87	8.07	5.43	2.72
PE190IGW50/V		3.54	90			87	6	145	10	1/8"	4.17	2.17	9.13		9.84		
PE190MGW65/V	2 1/2"	3.54	90	2.56	65	87	6	87	6	1/8"	4.17	2.17	10.43	1.02	11.2	7	3.35
PE1125MGW65/V		4.92	125			80	5.5	130	9	1/4"	6.69	3.35	12.40		12.9		
PE1125RGW80/V	3"	4.92	125	3.15	80	80	5.5	72.5	5	1/4"	6.69	3.35	12.87	1.06	15	8.27	3.94

